

## LEVPANO COMBI® Réf.: 517000

### Characteristics

For simple and safe intensive vertical installation  
3 installation options: horizontal, under slopes and vertical

**LOW LOADING HEIGHT**  
- 68 cm for the 4m model  
- 81cm for the 4.50m model

**ERGONOMIC HANDLEBARS - PATENTED**  
The handlebar makes handling the plates ultra-simple, and is equipped with 2 levers:  
- 1 for 90° pivoting of the beam and arms  
- 1 for tilting the head

**SAFETY SYSTEM** consisting of 2 cables - PATENTED  
- 1 working cable  
- 1 anti-fall safety cable

**FOLDING** and adjustable PADS for fitting plasterboard of all widths 0.60m, 0.90m and 1.20m - PATENTED

**FLOOR SPACE**  
- Horizontal installation and under slopes: 1.02 x 1.02 x 1.02 m  
- Vertical installation: 1.09 x 0.94 x 0.94 m

**EASY TO HANDLE**  
- Ergonomic handlebars for effortless handling of the panels  
- Braking system integrated into the non-return winch, attached to the guide handle. This makes the machine extremely manoeuvrable  
- 3 Ø 160 mm wheels for easy movement over rough surfaces, particularly with heavier fireproof panels or gypsum and cellulose boards, fitted with a locking system  
- 2 transport wheels for moving when closed  
- Low loading height

**GUARANTEED SAFETY**  
8 anti-slip pads to keep the plate firmly in place  
- Offset handle: the guide handle is not located under the plate. The user is off-set to give better visibility and more control. This also means you don't have to put your head under the Levpano when descending.

**PRACTICAL**  
- Quick to assemble and dismantle  
- A real platform on which you can climb to fix the plate.

**FEATURES**  
- Aluminium column for a payload of 80 kg  
- Platform: 0.50 x 0.62 m, thickness: 25 mm, height: 0.49 m and strength: 150 kg  
- Plasterboard of all widths: 0.60 m, 0.90 m and 1.20 m, thanks to the retractable and adjustable shoes on the Levpano arm (patented) and thanks to the adjustable arms opposite the shoes  
- Maximum opening of end arms: 3.10 m  
- Minimum height of horizontal plate: 1.19 m = work surface.

**OUR GUARANTEES :**  
- Complies with CE standards and European Directive 2006/42/EC  
- Compliance examination carried out by SOCOTEC  
- Each Levpano is individually assembled and tested  
- Delivered pre-assembled

**WORKPLATFORM** supplied with the appliance, adaptable to horizontal or under-roof configurations





**NOVALIA SAS** 2 rue de Bergognon 42500 LE CHAMBON F.  
FRANCE - [www.novalia.pro](http://www.novalia.pro)  
**PEDDINGHAUS** Handwerkzeuge In der Graslake 35  
58332 Schwelm DEUTSCHLAND - [www.peddinghaus.de](http://www.peddinghaus.de)  
**NOVALIA SA** Str. Narciselor nr.50 500251 - Braşov ROMÂNIA  
[www.mob-ius.ro](http://www.mob-ius.ro)  
**NOVALIA ESPAÑA** Portuete 51, of.204 20018 San Sebastián

## LEVPANO COMBI® Réf.: 517000



### Product data

Horizontal installation height m	Vertical installation height m	Loading height m	Platform height m	payload kg	 kg	G	Artikelnr.		EAN Code
4	5,40	0,68	0,49	80	53	5	516500	1	3479135165002
4,50	5,90	0,81	0,49	80	55	5	517000	1	3479135170006



**NOVALIA SAS** 2 rue de Bergognon 42500 LE CHAMBON F. FRANCE - [www.novalia.pro](http://www.novalia.pro)  
**PEDDINGHAUS** Handwerkzeuge In der Graslake 35 58332 Schwelm DEUTSCHLAND - [www.peddinghaus.de](http://www.peddinghaus.de)  
**NOVALIA SA** Str. Narciselor nr.50 500251 - Braşov ROMÂNIA [www.mob-ius.ro](http://www.mob-ius.ro)  
**NOVALIA ESPAÑA** Portuete 51, of.204 20018 San Sebastián